

FINAROL B 5746



Metalworking



Rust preventive oil « Prelube ».

UTILISATIONS

- **FINAROL B 5746** can be applied at ambient temperature by brush, dip, spray or electrostatic methods.
- **FINAROL B 5746** is a high performance corrosion preventive oil with metal-forming properties.

ADVANTAGES

- **FINAROL B 5746** is designed to fulfil the requirement of the steel and automotive industry.
- **FINAROL B 5746** provides:
 - Excellent corrosion protection on strip and sheet steel
 - Very good staining resistance, even after long term storage
 - Easy removal of the film by the conventional cleaning methods
 - Compatible with most refiner's oil to give a clear and uniform product
 - Good film-forming characteristics without any sign of dewetting during of after application.
 - Light planishing characteristics.
 - Very good press drawing properties.

TYPICAL CHARACTERISTICS	METHODS	UNITS	FINAROL B 5746
Appearance	visual	-	Brown, liquid
Density	ISO 12185	g/cm ³	0.904
Viscosity at 40 °C	ISO 3104	mm ² /s	9.75
Flash point	ISO 2592	°C	150
Humidity cabinet	DIN 50 017	Cycles	> 10
Exposure to HPLR 400 (during 168 h)	D 17 1785	%	No coloration
Natural exposition after 21 days	Internal	%	No staining

Above characteristics are mean values given as an information.