



TotalEnergies

Classic 5 15W-40

KEY DATA



LIGHT VEHICLE RANGE

INTERNATIONAL STANDARDS

- 💧 ACEA A3/B3
- 💧 API SL/CF

¹ Please refer to car owner's manual

CLASSIC, THE GUARANTEED QUALITY

Multigrade oil for all Gasoline and Diesel engines.

APPLICATIONS

All gasoline/Diesel engines: Particularly recommended for all gasoline and Diesel engines in cars and light vans. Permits use at all temperature, any type of service, in town or on the motorway.

CUSTOMERS BENEFITS

- 💧 Detergent capability: Detergent-dispersant capability keeping engine components clean and, in particular, preventing the formation of black sludge and the build-up of particles.
- 💧 Thermal stability: Good thermal stability and oxidation resistance preventing any premature damage at high temperature.
- 💧 Anti-wear: Good anti-wear properties, particularly in the timing system. Shear stability ensuring satisfactory lubrication in service.
- 💧 Lead free: Effective in engines using lead-free fuel and completely harmless to catalytic converters.

CHARACTERISTICS²

TEST	UNIT	RESULT
Viscosity grade	-	15W-40
Kinematic viscosity at 40°C	mm ² /s	113.4
Kinematic viscosity at 100°C	mm ² /s	13.9
Density at 15°C	kg/m ³	884
Viscosity index	-	136
Pour point	°C	-30
OC Flash point	°C	230

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.



TotalEnergies Lubrificants / Last update of this datasheet: June 22 / Classic 5 15W-40

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.